



**! COMPONENTS MARKED WITH THIS SYMBOL HAVE CRITICAL SPECIFICATIONS IMPORTANT FOR PROTECTION FROM FIRE AND ELECTRICAL SHOCK HAZARDS. WHEN SERVICING, IT IS ESSENTIAL THAT ONLY MANUFACTURER'S SPECIFIED PARTS BE USED FOR REPLACEMENT.**

PRIOR TO THE RETURN OF THIS APPLIANCE TO THE CUSTOMER AND UPON COMPLETION OF SERVICING, SERVICE PERSONNEL ARE REQUIRED TO TEST THIS UNIT FOR EQUIVALENT INSULATION RESISTANCE BETWEEN THE POWER SUPPLY AND EXPOSED PARTS

P4	
J6	
Y1	
TP3	
Q4	
VR2	
CR7	
C8	
R11	
<b>LAST USED</b>	<b>NOT USED</b>
<b>REFERENCE DESIGNATIONS</b>	

## NOTES:

- UNLESS OTHERWISE SPECIFIED:

  1. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W, 5%
  2. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS.
  3. ALL CERAMIC DISC CAPACITORS ARE +/-20%.
  4. ALL RADIAL ELECTROLYTIC CAPACITORS ARE +/-20%.
  5. \* DENOTES HEATSINK TO CHASSIS.
  6. POWER SWITCH IS SHOWN IN THE "OUT" POSITION.

# SCHEMATIC CONNECTOR AND SUPPLY BOARD

**AKG**  
acoustics

# SCHEMATIC CONNECTOR AND POWER SUPPLY BOARD

SCALE : <u>NONE</u>	SIZE <u>B</u>	NUMBER <u>61118-000</u>	REV <u>01</u>
SHEET <u>1</u> OF <u>1</u>			

卷之三